



tel: +46 8 793 05 90

smt.ssf@sandvik.com

Gällande leg.tillägg

Oktober 2016

Stång

| Legering | SEK | EUR |
|--------------------------------------|-------|------|
| EN 1.4307 - SANMAC 304L - ASTM 304L | 10,64 | 1,12 |
| EN 1.4404 - SANMAC 316L - ASTM 316L | 14,02 | 1,47 |
| EN 1.4571 - SANMAC 4571 - ASTM 316Ti | 14,32 | 1,51 |
| EN 1.4462 - SANMAC 2205 | 11,92 | 1,25 |
| EN 1.4410 - SAF 2507 | 14,32 | 1,51 |
| EN 1.4501 - SAF 32760 | 14,54 | 1,53 |
| EN 1.4460 - SANMAC 329 | 10,00 | 1,05 |

Ämnesrör

| Legering | SEK | EUR |
|--------------------------------------|-------|------|
| EN 1.4307 - SANMAC 304L - ASTM 304L | 10,54 | 1,11 |
| EN 1.4404 - SANMAC 316L - ASTM 316L | 14,62 | 1,54 |
| EN 1.4571 - SANMAC 4571 - ASTM 316Ti | 14,62 | 1,54 |
| EN 1.4462 - SANMAC 2205 | 12,57 | 1,32 |

Sömlösa rör

| Legering | SEK | | EUR | |
|---------------------------------------|------------|---------------|------------|---------------|
| | Extruderat | Kallbearbetat | Extruderat | Kallbearbetat |
| EN 1.4306 - SANDVIK 3R12 - ASTM 304L | 10,54 | 11,75 | 1,11 | 1,24 |
| EN 1.4404 - SANDVIK 3R650 - ASTM 316L | 14,62 | 16,30 | 1,54 | 1,71 |
| EN 1.4435 - SANDVIK 3R60 - ASTM 316L | 15,66 | 17,46 | 1,65 | 1,84 |
| EN 1.4571 - SANDVIK 5R75 - ASTM 316Ti | 14,62 | 16,30 | 1,54 | 1,71 |
| EN 1.4539 - SANDVIK 2RK65 - (904L) | 26,23 | 29,24 | 2,76 | 3,07 |
| EN 1.4563 - SANICRO 28 | 29,03 | 32,36 | 3,05 | 3,40 |
| Alloy 625 - SANICRO 60 | 55,87 | 62,29 | 5,87 | 6,55 |
| EN 1.4362 - SANDVIK SAF 2304 | 8,02 | 8,94 | 0,84 | 0,94 |
| EN 1.4462 - SANDVIK SAF 2205 | 12,57 | 14,01 | 1,32 | 1,47 |
| EN 1.4410 - SANDVIK SAF 2507 | 14,62 | 16,30 | 1,54 | 1,71 |
| EN 1.4547 - 254 SMO** | 24,02 | 26,78 | 2,52 | 2,82 |
| SANDVIK 4C54 | 5,30 | 5,91 | 0,56 | 0,62 |
| SANDVIK 7RE10 - 310S, 310H | 17,04 | 19,00 | 1,79 | 2,00 |
| SANDVIK 253 MA** | 11,15 | 12,43 | 1,17 | 1,31 |
| SANDVIK 353 MA** | 26,97 | 30,07 | 2,83 | 3,16 |

Svetsade rör

| Legering | SEK | EUR |
|------------------------|-------|------|
| EN 1.4307 - ASTM 304L | 12,37 | 1,30 |
| EN 1.4541 - ASTM 321 | 12,37 | 1,30 |
| EN 1.4404 - ASTM 316L | 16,27 | 1,71 |
| EN 1.4571 - ASTM 316Ti | 16,48 | 1,73 |
| EN 1.4462 | 13,92 | 1,46 |

Rördelar & Flänsar

| Legering | Gängrördelar | Svetsrördelar | Flänsar |
|-----------------------|--------------|---------------|---------|
| | AAF* | AAF* | AAF* |
| EN 1.4307 - ASTM 304L | 33% | 33% | 33% |
| EN 1.4404 - ASTM 316L | 36% | 36% | 36% |
| EN 1.4462 | | 36% | 36% |

* AAF = Alloy adjustment factor, ** 253 MA, 353 MA, 254 SMO are trademarks owned by Outokumpu OY