

STRIP  
ALLOY & ENERGY SURCHARGE

VALID FOR INVOICING: May

With process factor valid for finished cold rolled and hardened and tempered strip products

Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

Sandvik	GRADE		ALLOY & ENERGY SURCHARGE PER KG										
	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF	Lbs USD	Lbs CAD
<b>Alloyed non-stainless steels and carbon steels</b>													
15LM	1.1248	1074	1770	9,81	0,95	0,79	1,04	127,34	1,31	6,61	0,97	0,47	0,59
20C	1.1274	1095	1870	9,94	0,96	0,80	1,05	128,91	1,32	6,70	0,98	0,48	0,60
20C2			2258	10,71	1,03	0,86	1,13	138,92	1,43	7,22	1,06	0,51	0,65
25C				9,91	0,96	0,80	1,05	128,58	1,32	6,68	0,98	0,48	0,60
10C16Mo3V1				22,77	2,20	1,84	2,41	295,35	3,03	15,34	2,25	1,09	1,37
Sanprint XP				20,78	2,01	1,68	2,20	269,54	2,77	14,00	2,05	1,00	1,25
****													
<b>Martensitic stainless chromium steels</b>													
6C27	1.4007	420	2234	18,52	1,79	1,50	1,96	240,26	2,47	12,48	1,83	0,89	1,12
7C27Mo2				24,03	2,32	1,94	2,55	311,76	3,20	16,19	2,37	1,15	1,45
10C28MO2				24,35	2,35	1,97	2,58	315,89	3,24	16,41	2,41	1,17	1,47
12C27M				19,03	1,84	1,54	2,02	246,88	2,53	12,82	1,88	0,91	1,15
12C27				18,42	1,78	1,49	1,95	239,02	2,45	12,42	1,82	0,89	1,11
14C28N				18,71	1,81	1,51	1,98	242,74	2,49	12,61	1,85	0,90	1,13
13C26				18,04	1,74	1,46	1,91	234,05	2,40	12,16	1,78	0,87	1,09
19C27				18,42	1,78	1,49	1,95	239,02	2,45	12,42	1,82	0,89	1,11
****													
<b>Austenitic stainless steels</b>													
12R11	1.4310	301	2331	49,73	4,80	4,02	5,27	645,19	6,62	33,51	4,91	2,39	3,00
11R51	1.4310	301	2231	53,21	5,14	4,30	5,64	690,31	7,08	35,86	5,26	2,56	3,21
13RM19	EN 1.4369			50,29	4,85	4,06	5,33	652,43	6,70	33,89	4,97	2,42	3,04
316LVM	1,4441	316LVM		93,17	8,99	7,52	9,87	1 208,71	12,40	62,79	9,21	4,48	5,63
2RK65HV				141,39	13,65	11,42	14,98	1 834,37	18,82	95,29	13,97	6,79	8,54
3X8R65				72,78	7,02	5,88	7,71	944,28	9,69	49,05	7,19	3,50	4,40
****													
<b>Precipitation hardenable steels</b>													
9RU10	1.4568	631	2388	50,47	4,87	4,08	5,35	654,79	6,72	34,01	4,99	2,42	3,05
NANOFLEX				75,94	7,33	6,13	8,04	985,21	10,11	51,18	7,50	3,65	4,59
1RK95				50,60	4,88	4,09	5,36	656,53	6,74	34,10	5,00	2,43	3,06
****													
<b>Duplex stainless steels (austenitic-ferritic)</b>													
SAF2205	EN 1.4462		2377	63,82	6,16	5,15	6,76	827,96	8,50	43,01	6,31	3,07	3,85
SAF2507	EN 1.4410		2328	74,54	7,19	6,02	7,90	967,11	9,92	50,24	7,37	3,58	4,50
SAF3207HD				76,48	7,38	6,18	8,10	992,29	10,18	51,54	7,56	3,67	4,62
****													
<b>Ferritic stainless chromium steel</b>													
1C429				24,80	2,39	2,00	2,63	321,74	3,30	16,71	2,45	1,19	1,50
1C44Mo20				29,45	2,84	2,38	3,12	382,07	3,92	19,85	2,91	1,41	1,78
0XC34				20,65	1,99	1,67	2,19	267,97	2,75	13,92	2,04	0,99	1,25
1C34				20,53	1,98	1,66	2,17	266,32	2,73	13,83	2,03	0,99	1,24
****													
<b>Nickel-base alloy</b>													
SANICRO75X2	UNS N07750			306,78	29,61	24,78	32,49	3 980,16	40,84	206,75	30,31	14,74	18,53
SAN62TiNb				266,96	25,77	21,56	28,27	3 463,43	35,54	179,91	26,38	12,83	16,12
****													
<b>Energy surcharge per kg included in total surcharge</b>				2,41	0,23	0,19	0,26	31,25	0,32	1,62	0,24	0,12	0,15