



# SANDVIK 4XC26 BILLETS

## DATASHEET

Sandvik 4XC26 is a martensitic stainless chromium steel with a low carbon content that is characterized by excellent formability. After hardening, the grade has good corrosion resistance and high toughness.

### STANDARDS

- ASTM: 420
- UNS: S42000
- EN Number: 1.4021
- W.Nr.: 1.4021
- SS: 2303
- AFNOR: Z20C13
- BS: 420S29

### Certificates

Status according to EN 10 204 3.1

### CHEMICAL COMPOSITION (NOMINAL) %

C	Si	Mn	P	S	Cr	Ni	Mo	Others
0.20	0.3	0.9	≤0.020	≤0.010	13	-	-	-

### FORMS OF SUPPLY

#### Sizes and tolerances

Round-cornered square, as well as round billets, are produced in a wide range of sizes according to the following tables. Larger sizes offered on request.

#### Surface conditions

##### Square billets

Unground, spot ground or fully ground condition.

##### Round billets

Peel turned or black condition.

#### Square billets

Size	Tolerance	Length
mm	mm	m
80	+/-2	4 - 6.3

## Square billets

Size	Tolerance	Length
mm	mm	m
100, 114, 126, 140, 150	+/-3	4 - 6.3
160, 180, 195, 200	+/-4	4 - 6.3
>200 - 350	+/-5	3 - 5.3

Sizes and tolerances apply to the rolled/forged condition.

## Peel turned round billets

Size	Tolerance	Length
mm	mm	m
75 - 200 (5 mm interval)	+/-1	max 10
>200 - 450	+/-3	3 - 8

## Unground round billets

Size	Tolerance	Length
mm	mm	m
77 - 112 (5 mm interval)	+/-2	max 10
124, 134	+/-2	max 10
127, 147, 157	+/-2	max 10
142, 152, 163	+/-2	max 10
168, 178, 188	+/-2	max 10
183, 193	+/-2	max 10

## Other products

- Hollow bar

Disclaimer: Recommendations are for guidance only, and the suitability of a material for a specific application can be confirmed only when we know the actual service conditions. Continuous development may necessitate changes in technical data without notice. This datasheet is only valid for Sandvik materials.