

Gällande leg.tillägg

Juni 2017

Stång

| Legering | SEK | EUR |
|--------------------------------------|-------|------|
| EN 1.4307 - SANMAC 304L - ASTM 304L | 13,35 | 1,39 |
| EN 1.4404 - SANMAC 316L - ASTM 316L | 17,59 | 1,83 |
| EN 1.4571 - SANMAC 4571 - ASTM 316Ti | 17,82 | 1,85 |
| EN 1.4462 - SANMAC 2205 | 16,72 | 1,74 |
| EN 1.4410 - SAF 2507 | 19,82 | 2,06 |
| EN 1.4501 - SAF 32760 | 20,21 | 2,10 |
| EN 1.4460 - SANMAC 329 | 14,60 | 1,52 |

Ämnesrör

| Legering | SEK | EUR |
|--------------------------------------|-------|------|
| EN 1.4307 - SANMAC 304L - ASTM 304L | 13,31 | 1,38 |
| EN 1.4404 - SANMAC 316L - ASTM 316L | 18,35 | 1,90 |
| EN 1.4571 - SANMAC 4571 - ASTM 316Ti | 18,35 | 1,90 |
| EN 1.4462 - SANMAC 2205 | 17,94 | 1,86 |

Sömlösa rör

| Legering | Extruderat | | Kallbearbetat | |
|---------------------------------------|------------|------|---------------|------|
| | SEK | EUR | SEK | EUR |
| EN 1.4306 - SANDVIK 3R12 - ASTM 304L | 13,31 | 1,38 | 14,84 | 1,54 |
| EN 1.4404 - SANDVIK 3R650 - ASTM 316L | 18,35 | 1,90 | 20,46 | 2,12 |
| EN 1.4435 - SANDVIK 3R60 - ASTM 316L | 19,41 | 2,01 | 21,64 | 2,25 |
| EN 1.4571 - SANDVIK 5R75 - ASTM 316Ti | 18,35 | 1,90 | 20,46 | 2,12 |
| EN 1.4539 - SANDVIK 2RK65 - (904L) | 30,41 | 3,16 | 33,90 | 3,52 |
| EN 1.4563 - SANICRO 28 | 33,34 | 3,46 | 37,17 | 3,86 |
| Alloy 625 - SANICRO 60 | 59,33 | 6,16 | 66,15 | 6,87 |
| EN 1.4362 - SANDVIK SAF 2304 | 12,09 | 1,25 | 13,48 | 1,40 |
| EN 1.4462 - SANDVIK SAF 2205 | 17,94 | 1,86 | 20,00 | 2,08 |
| EN 1.4410 - SANDVIK SAF 2507 | 20,63 | 2,14 | 23,00 | 2,39 |
| EN 1.4547 - 254 SMO** | 29,52 | 3,06 | 32,91 | 3,42 |
| SANDVIK 4C54 | 10,40 | 1,08 | 11,59 | 1,20 |
| SANDVIK 7RE10 - 310S, 310H | 19,81 | 2,06 | 22,09 | 2,29 |
| SANDVIK 253 MA** | 14,37 | 1,49 | 16,02 | 1,66 |
| SANDVIK 353 MA** | 29,09 | 3,02 | 38,11 | 3,37 |
| Alloy 825 - SANICRO 41 | 34,19 | 3,55 | 38,11 | 3,96 |

Svetsade rör

| Legering | SEK | EUR |
|------------------------|-------|------|
| EN 1.4307 - ASTM 304L | 14,86 | 1,54 |
| EN 1.4541 - ASTM 321 | 14,85 | 1,54 |
| EN 1.4404 - ASTM 316L | 19,95 | 2,07 |
| EN 1.4571 - ASTM 316Ti | 20,15 | 2,09 |
| EN 1.4462 | 19,16 | 1,99 |

Rördelar & Flänsar

| Legering | Gängrördelar | Svetsrördelar | Flänsar |
|-----------------------|--------------|---------------|---------|
| | AAF* | AAF* | AAF* |
| EN 1.4307 - ASTM 304L | 40% | 40% | 40% |
| EN 1.4404 - ASTM 316L | 44% | 44% | 44% |
| EN 1.4462 | | 44% | 44% |

* AAF = Alloy adjustment factor, ** 253 MA, 353 MA, 254 SMO are trademarks owned by Outokumpu OY