

STRIP  
ALLOY SURCHARGE

**VALID FOR INVOICING: October**

With process factor valid for finished cold rolled and hardened and tempered strip products  
Since January 2016 a time lag of 45 days between market alloy prices and its alloy surcharge is used. Currency exchange rates for corresponding time period.

Sandvik	GRADE		ALLOY SURCHARGE PER KG										Lbs USD	Lbs CAD
	W.nr	ASTM	SS	SEK	EUR	GBP	USD	JPY	CAD	CNY	CHF			
<b>Alloyed non-stainless steels and carbon steels</b>														
15LM	1.1248	1074	1770	2,16	0,20	0,18	0,22	23,69	0,30	1,58	0,22	0,10	0,13	
20C	1.1274	1095	1870	2,19	0,20	0,18	0,23	24,07	0,30	1,61	0,22	0,10	0,14	
20C2			2258	2,41	0,22	0,20	0,25	26,47	0,33	1,77	0,24	0,11	0,15	
25C				2,18	0,20	0,18	0,23	23,99	0,30	1,60	0,22	0,10	0,14	
10C16Mo3V1				7,80	0,73	0,66	0,80	85,66	1,07	5,72	0,79	0,36	0,48	
Sanprint XP				7,37	0,69	0,62	0,76	81,01	1,01	5,41	0,75	0,34	0,46	
****														
<b>Martensitic stainless chromium steels</b>														
6C27	1.4007	420	2234	4,62	0,43	0,39	0,48	50,80	0,63	3,39	0,47	0,22	0,29	
7C27Mo2				7,59	0,71	0,64	0,78	83,42	1,04	5,57	0,77	0,36	0,47	
10C28MO2				7,68	0,72	0,65	0,79	84,41	1,05	5,64	0,78	0,36	0,48	
12C27M				4,77	0,44	0,40	0,49	52,39	0,65	3,50	0,48	0,22	0,30	
12C27				4,60	0,43	0,39	0,47	50,50	0,63	3,37	0,47	0,22	0,29	
14C28N				4,68	0,44	0,39	0,48	51,40	0,64	3,43	0,48	0,22	0,29	
13C26				4,49	0,42	0,38	0,46	49,31	0,61	3,29	0,46	0,21	0,28	
19C27				4,60	0,43	0,39	0,47	50,50	0,63	3,37	0,47	0,22	0,29	
****														
<b>Austenitic stainless steels</b>														
12R11	1.4310	301	2331	18,51	1,73	1,56	1,91	203,41	2,53	13,59	1,88	0,87	1,15	
11R51	1.4310	301	2231	20,48	1,91	1,73	2,11	225,07	2,80	15,04	2,08	0,96	1,27	
13RM19	EN 1.4369			18,60	1,74	1,57	1,92	204,39	2,55	13,65	1,89	0,87	1,15	
316LVM	1,4441	316LVM		39,53	3,69	3,34	4,08	434,34	5,41	29,02	4,02	1,85	2,45	
2RK65HV				61,89	5,77	5,23	6,38	680,06	8,47	45,43	6,29	2,90	3,84	
3X8R65				29,93	2,79	2,53	3,09	328,92	4,10	21,97	3,04	1,40	1,86	
****														
<b>Precipitation hardenable steels</b>														
9RU10	1.4568	631	2388	18,89	1,76	1,60	1,95	207,62	2,59	13,87	1,92	0,88	1,17	
NANOFLEX				32,77	3,06	2,77	3,38	360,14	4,48	24,06	3,33	1,53	2,03	
1RK95				19,52	1,82	1,65	2,01	214,49	2,67	14,33	1,98	0,91	1,21	
****														
<b>Duplex stainless steels (austenitic-ferritic)</b>														
SAF2205	EN 1.4462		2377	25,76	2,40	2,18	2,66	283,08	3,52	18,91	2,62	1,21	1,60	
SAF2507	EN 1.4410		2328	30,61	2,86	2,58	3,16	336,38	4,19	22,47	3,11	1,43	1,90	
SAF3207HD				30,63	2,86	2,59	3,16	336,54	4,19	22,48	3,11	1,43	1,90	
****														
<b>Ferritic stainless chromium steel</b>														
1C429				6,40	0,60	0,54	0,66	70,36	0,88	4,70	0,65	0,30	0,40	
1C44Mo20				9,13	0,85	0,77	0,94	100,30	1,25	6,70	0,93	0,43	0,57	
0XC34				5,23	0,49	0,44	0,54	57,45	0,72	3,84	0,53	0,24	0,32	
1C34				5,19	0,48	0,44	0,54	57,05	0,71	3,81	0,53	0,24	0,32	
****														
<b>Nickel-base alloy</b>														
SANICRO75X2	UNS N07750			136,06	12,69	11,49	14,03	1 495,10	18,62	99,88	13,82	6,37	8,44	
SAN62TiNb				117,87	11,00	9,95	12,16	1 295,15	16,13	86,52	11,97	5,51	7,32	
****														