



Seosainelisät

terasmyynti@sandvik.com
Joulukuu 2018

Pyörötangot

| Teräslaatu | EUR/kg |
|--------------------------------------|--------|
| EN 1.4307 - SANMAC 304L - ASTM 304L | 1,45 |
| EN 1.4404 - SANMAC 316L - ASTM 316L | 2,18 |
| EN 1.4571 - SANMAC 4571 - ASTM 316Ti | 2,23 |
| EN 1.4462 - SANMAC 2205 | 1,98 |
| EN 1.4410 - SAF 2507 | 2,38 |
| EN 1.4501 - SAF 32760 | 2,41 |
| EN 1.4460 - SANMAC 329 | 1,57 |

Ainesputket

| Teräslaatu | EUR/kg |
|--------------------------------------|--------|
| EN 1.4307 - SANMAC 304L - ASTM 304L | 1,62 |
| EN 1.4404 - SANMAC 316L - ASTM 316L | 2,41 |
| EN 1.4571 - SANMAC 4571 - ASTM 316Ti | 2,41 |
| EN 1.4462 - SANMAC 2205 | 2,22 |
| EN 1.4460 - SANDVIK 10RE51 | 1,75 |

Saumattomat putket Huom. Purs.=pursotettu Kylmä = kylmäuokattu

| Teräslaatu | Purs. | EUR/kg | Kvlmä |
|---------------------------------------|-------|--------|-------|
| EN 1.4306 - SANDVIK 3R12 - ASTM 304L | 1,62 | | 1,80 |
| EN 1.4404 - SANDVIK 3R65 - ASTM 316L | 2,41 | | 2,69 |
| EN 1.4435 - SANDVIK 3R60 - ASTM 316L | 2,59 | | 2,89 |
| EN 1.4571 - SANDVIK 5R75 - ASTM 316Ti | 2,41 | | 2,69 |
| EN 1.4539 - SANDVIK 2RK65 - (904L) | 4,28 | | 4,78 |
| EN 1.4563 - SANICRO 28 | 4,58 | | 5,11 |
| Alloy 625 - SANICRO 60 | 8,90 | | 9,92 |
| EN 1.4362 - SANDVIK SAF 2304 | 1,29 | | 1,43 |
| EN 1.4462 - SANDVIK SAF 2205 | 2,22 | | 2,47 |
| EN 1.4410 - SANDVIK SAF 2507 | 2,56 | | 2,86 |
| EN 1.4547 - 254 SMO** | 4,12 | | 4,60 |
| SANDVIK 4C54 | 0,88 | | 0,98 |
| SANDVIK 7RE10 - ASTM 310S, ASTM 310H | 2,50 | | 2,79 |
| SANDVIK 253 MA** | 1,70 | | 1,90 |
| SANDVIK 353 MA** | 3,97 | | 4,43 |

* AAF = Alloy adjustment factor, ** 253 MA, 353 MA, 254 SMO are trademarks owned by Outokumpu OY