



Seosainelisät

terasmyynti@sandvik.com
Tammikuu 2019

Pyörötangot

| Teräslaatu | EUR/kg |
|--------------------------------------|--------|
| EN 1.4307 - SANMAC 304L - ASTM 304L | 1,42 |
| EN 1.4404 - SANMAC 316L - ASTM 316L | 2,06 |
| EN 1.4571 - SANMAC 4571 - ASTM 316Ti | 2,10 |
| EN 1.4462 - SANMAC 2205 | 1,92 |
| EN 1.4410 - SAF 2507 | 2,30 |
| EN 1.4501 - SAF 32760 | 2,34 |
| EN 1.4460 - SANMAC 329 | 1,52 |

Ainesputket

| Teräslaatu | EUR/kg |
|--------------------------------------|--------|
| EN 1.4307 - SANMAC 304L - ASTM 304L | 1,48 |
| EN 1.4404 - SANMAC 316L - ASTM 316L | 2,26 |
| EN 1.4571 - SANMAC 4571 - ASTM 316Ti | 2,26 |
| EN 1.4462 - SANMAC 2205 | 2,14 |
| EN 1.4460 - SANDVIK 10RE51 | 1,69 |

Saumattomat putket Huom. Purs.=pursotettu Kylmä = kylmäuokattu

| Teräslaatu | Purs. | EUR/kg | Kylmä |
|---------------------------------------|-------|--------|-------|
| EN 1.4306 - SANDVIK 3R12 - ASTM 304L | 1,48 | | 1,65 |
| EN 1.4404 - SANDVIK 3R65 - ASTM 316L | 2,26 | | 2,51 |
| EN 1.4435 - SANDVIK 3R60 - ASTM 316L | 2,43 | | 2,70 |
| EN 1.4571 - SANDVIK 5R75 - ASTM 316Ti | 2,26 | | 2,51 |
| EN 1.4539 - SANDVIK 2RK65 - (904L) | 3,98 | | 4,43 |
| EN 1.4563 - SANICRO 28 | 4,21 | | 4,69 |
| Alloy 625 - SANICRO 60 | 8,14 | | 9,08 |
| EN 1.4362 - SANDVIK SAF 2304 | 1,22 | | 1,36 |
| EN 1.4462 - SANDVIK SAF 2205 | 2,14 | | 2,39 |
| EN 1.4410 - SANDVIK SAF 2507 | 2,47 | | 2,76 |
| EN 1.4547 - 254 SMO** | 3,90 | | 4,35 |
| SANDVIK 4C54 | 0,87 | | 0,96 |
| SANDVIK 7RE10 - ASTM 310S, ASTM 310H | 2,26 | | 2,52 |
| SANDVIK 253 MA** | 1,56 | | 1,74 |
| SANDVIK 353 MA** | 3,55 | | 3,95 |

* AAF = Alloy adjustment factor, ** 253 MA, 353 MA, 254 SMO are trademarks owned by Outokumpu OY